

CERTIFICATE OF CONFORMITY

Certificate No.: 17864-1S

Date Issued: November 19, 2019

Project No.: 17864

Certification System Type 3
(ISO / IEC Guide 67)

Client No.: LC1231751

Applicant: Victron Energy B.V.
De Paal 35
1351 JG Almere Haven
The Netherlands



A handwritten signature in blue ink, which appears to read 'Kavinder Dhillon', is written over a horizontal line.

Issued by: _____
Certification Manager

Products: Battery Charger

Model No(s): Blue Smart IP65 Charger 12/10 (1)
Blue Smart IP65 Charger 12/5 (1)
Blue Smart IP65 Charger 12/15 (1)
Blue Smart IP65 Charger 24/5 (1)
Blue Smart IP65 Charger 24/8 (1)
Blue Smart IP67 Charger 12/17 (1)
Blue Smart IP67 Charger 12/25 (1)
Blue Smart IP67 Charger 24/8 (1)
Blue Smart IP67 Charger 24/12 (1)
Blue Smart IP67 Charger 12/7 (1)
Blue Smart IP67 Charger 12/13 (1)
Blue Smart IP67 Charger 24/5 (1)

The 'C' and 'US' indicators adjacent to the LabTest Certification Mark shall signify that the product has been evaluated by an accredited laboratory to the applicable Canadian and US Standards. The subject area shall be displayed with the LabTest Certification Mark to identify the Standard Number, and Revision Level.

Ratings:

- Blue Smart IP65 Charger 12/10 (1)-120V NEMA 1-15
Input: 110-130Vac, 50-60Hz; Output: 12Vdc, 10A
- Blue Smart IP65 Charger 12/5 (1)
Input: 110-130Vac, 50-60Hz; Output: 12Vdc, 5A
- Blue Smart IP65 Charger 12/15 (1)-120V NEMA 1-15
Input: 110-130Vac, 50-60Hz; Output: 12Vdc, 15A
- Blue Smart IP65 Charger 24/5 (1)-120V NEMA 1-15
Input: 110-130Vac, 50-60Hz; Output: 24Vdc, 5A
- Blue Smart IP65 Charger 24/8 (1)-120V NEMA 1-15
Input: 110-130Vac, 50-60Hz; Output: 24Vdc, 8A
- Blue Smart IP67 Charger 12/17 (1)-120V NEMA 5-15
Input: 110-130Vac, 50-60Hz; Output: 12Vdc, 17A
- Blue Smart IP67 Charger 12/25 (1)-120V NEMA 5-15
Input: 110-130Vac, 50-60Hz; Output: 12Vdc, 25A
- Blue Smart IP67 Charger 24/8 (1)-120V NEMA 5-15
Input: 110-130Vac, 50-60Hz; Output: 24Vdc, 8A
- Blue Smart IP67 Charger 24/12 (1)-120V NEMA 5-15
Input: 110-130Vac, 50-60Hz; Output: 24Vdc, 12A
- Blue Smart IP67 Charger 12/7 (1)-120V NEMA 5-15
Input: 110-130Vac, 50-60Hz; Output: 12Vdc, 7A
- Blue Smart IP67 Charger 12/13 (1)-120V NEMA 5-15
Input: 110-130Vac, 50-60Hz; Output: 12Vdc, 13A
- Blue Smart IP67 Charger 24/5 (1)-120V NEMA 5-15
Input: 110-130Vac, 50-60Hz; Output: 24Vdc, 5A

Applicable requirements:

- UL 1236 (Edition 8)
- CSA-C22.2 No. 107.2-01 (R2016)

Conditions of acceptability:

- None